



MODULAR POS SYSTEM



B180



B180 Datasheet



System Configuration

Intel® Processor	Intel Celeron J1900 Quad Core CPU 2M Cache, 2GHz up to 2.42 GHz		
Memory	DDR3L 1333MHz SO-DIMM x 1, Default 2G, max. 4GB		
Storage	SATA 2.5" hard drives (HDD) or flash storage (SSD or mSATA SSD)		
Power Supply	DC12V/5A external power adapter. AC100 to 240V full range.		
O/S Compatibility	Windows 7, POS Ready7, Windows 8.1, Industry Pro Retail 8.1, Windows 10IoT		
Physical Dimensions (W*H*D)	Width: 245mm / Height: 48mm / Depth: 194mm		
System Weight(with stand)	1.6Kg		
Wall Mount	VESA 100*100mm compliant or Wall Mount Kit		
Product Certification	CE / FCC / BSMI		
Operation Temperature	0°C to 40°C	Storage Temperature	-25°C to 70°C/td>
Humidity	15% ~ 80%		

I/O Connectivity

Parallel	1 port DB-25 Printer Port (Standard)		
USB	6 port , 6 x USB 2.0		
LAN	1 port RJ-45 LAN with activity and link LEDs 10/100/1000 Gb Ethernet		
SERIAL	4 x DB-9, COM1 & COM3		
Cash DRAWER	1 port RJ11 / Supports 2 Cash Drawer(12V)		
AUDIO	HD Audio, 3W Speaker(Optional), 1 x Line out, 1 x Mic In		
VGA	1 port DB-15		
DC12V out (for P2+ monitors)	1 port DC+12v/1A out Jack		
PS/2	1 port PS/2 KB		
Extension Slot	mini-PCI-e slot x 1		

Option

M115 Monitor	15" Standalone Touch Monitor 1024 x 768, VGA Interface		
HDMI Port	HDMI x 1(via VGA to HDMI converter)		
2nd VGA Port	By Factory Setup (Either VGA-2 or COM 4) MOQ		
WiFi	WiFi 802.11 b/g/n.		
SSD HDD	SATA 2.5" ,Minimum 32GB		

Product specifications subject to change without prior notice.

Certifications



POS SOLUTIONS PVT LTD
 306, 3rd floor, Sanjar Enclave,
 Opp. Milap PVR Cinema,
 S.V. Road, Kandivali (W),
 Mumbai—400067. India.
 Tel: 8767059495/069495/079495

